TREE BUBBLERS



Specifications

Flow Rate:

TB-05: 0.5 GPM (0,114 m³/h; 1,9 l/m) TB-10: 1.0 GPM (0,227 m³/h; 3,8 l/m) TB-20: 2.0 GPM (0,454 m³/h; 7,6 l/m)

TB-ADJ: 1.36 – 5.9 GPM (0,31 – 1,34 m³/h; 5 – 22 l/m)

■ Operating Pressure: 20 – 50 PSI (1,4 – 2,8 bar)

Spacing: 1' - 3' (0,3 m - 0,9 m)
Inlet: 1/2" (1,3 cm) Female Thread

Umbrella Pattern

TB-ADJ Adjustable Bubbler

Models

TB-05

TB-10

TB-20



TB-025 0.25 GPM (0, 95 LPM) Bubbler

0.5 GPM (1,9 LPM) Bubbler

1.0 GPM (3,8 LPM) Bubbler

2.0 GPM (7,6 LPM) Bubbler



SHRUB ADAPTERS

K-Rain Shrub Adapters are available for both male and female threaded nozzles. They are manufactured with high quality, UV inhibitor-infused ABS plastic for long life.

Specifications

- Adapts K-Rain nozzles for use with 1/2" threaded risers.
- Accepts protective, non-clogging K-Rain filters (shipped with nozzle)
- Durable, non-corrosive plastic construction

Models

PSA ShrubAdapter, Female Thread

(for male nozzles)

PFSA Shrub Adapter, Male Thread

(for female nozzles)

Female Shrub Adapter



Male Shrub Adapter





K-Rain Manufacturing Corp.

1640 Australian Avenue Riviera Beach, FL 33404 USA 561.844.1002

FAX: 561.842.9493

1.800.735.7246 | www.krain.com